

Océ TDS320 Specifications

System Data



Océ TDS320

Effortless workflow, true reliability

Océ TDS320 printer technology

<i>Technology</i>	Electrophotography (LED) with Organic Photoconductor drum
<i>Resolution</i>	600 dpi
<i>Printer optimization</i>	User specified print optimization modes: Line & Text for excellent line accuracy; Standard for excellent lines plus smooth grays; Poster for excellent grays and smooth solid fills
<i>Fusing technology</i>	Océ Radiant Fusing, instant-on
<i>Toner system</i>	Clean closed toner system, refill while printing

Throughput

<i>Speed</i>	Constant 9 linear ft./min. or 1.8 E size/min. in all print modes
<i>Warm-up time</i>	None, instant-on
<i>Paper path</i>	Optimized, continuous printing speed when printing jobs from different rolls



Media

<i>Media sources</i>	Choice of 1 or 2 roll version plus manual feed; 2 roll version includes integrated stacker for up to 100 prints
<i>Media capacity</i>	Up to 500 ft. per roll with automatic roll switching
<i>Media types</i>	Plain, transparent, recycled, fluorescent and colored paper, films and vellums
<i>Media trimming</i>	Closed system protects cutting device
<i>Output sizes</i>	From "B" to "E" and 36", up to 49 ft. long



Océ TDS320 specifications

Environment

<i>Dimensions</i>	53.5" (W) × 40" (D) × 50" (H)
<i>Weight</i>	Approximately 386 lbs. (1 roll version) 408 lbs. (2 roll version)
<i>Main supply</i>	100/120/230 V, 50/60 Hz
<i>Power consumption</i>	EPA Energy Star® compliant, Operating 1340 W, Standby 28 W and Sleep mode 6 W
<i>Sound pressure</i>	Sleep mode 0 dB (A), Standby 24 dB (A) Operating 54 dB (A) according to EN7779 operator position
<i>Safety approvals</i>	TüV GS, CETECOM, CE, (c)UL, FCC°

Océ Power Logic® controller

<i>Platform</i>	Océ Controller with Windows®XP embedded
<i>Memory</i>	512 Mb, expandable to 1.024 Mb
<i>Graphic user interface</i>	Optional monitor
<i>Interfaces</i>	Standard: Ethernet 100/10 Mbits/s. with RJ45
<i>Network protocols</i>	TCP/IP, NetBEUI (smb), Novell (IPX/SPX), FTP, LPD; other protocols supported through an external print server
<i>Power consumption</i>	< 62.5 W controller
<i>Main supply</i>	120/230 V, 50/60 Hz
<i>File formats</i>	HPGL, HPGL2, Calcomp 906/907/951 HPRTL, TIFF 6.0, CALS1, NIRS, C4, ASCII, optional Adobe® PostScript® 3™/PDF
<i>Functionality</i>	<ul style="list-style-type: none">■ File spooling on the controller■ Concurrent receiving / processing / printing■ Océ Settings Editor application: edit and save customized system settings■ Special modes: Standard, Line & Text and Poster■ Multiple prints: up to 999■ Automatic language sensing■ Automatic roll selection and switching■ Plot manipulation: rotation, autoscaling and positioning■ Pen management

Océ Remote Logic® application

Local and remote user communication system with:

<i>Settings Editor</i>	Edit and save customized system settings application:
<i>Supported operating systems</i>	Windows 98, Me, 2000, NT4.0 SP3 and XP; on any other platform and operating system supporting Java 1.1.8 or higher

Océ TDS320 scanner

<i>Technology</i>	CCD, Océ Image Logic® real time image processing hardware
<i>Speed</i>	9 linear ft./min.
<i>Original feed</i>	Face down, right aligned. Automatic feed on/off. Rewind original to front on/off.
<i>Originals</i>	Image width: 8.5" - 36" Original width: 8.5" - 40" Original length: 8.5" - 49 ft.
<i>Exposure control</i>	Automatic background compensation (on/off) manual fine adjustment
<i>Special modes</i>	Line & Text, Photo and Blueprint
<i>Reproduction scale</i>	25% to 400%, adjustable in 1% and programmable fixed steps
<i>Scan-to-file zoom</i>	50% to 200%
<i>Other operating functions</i>	<ul style="list-style-type: none">■ Concurrent copying and printing■ Multicopy mode: 1-99 copies (scan once print many)■ Programmable default settings■ Standard cut or synchro cut modes■ Leading- and trailing-edge adjustment (add or remove up to 15.7")■ Image mirroring
<i>Power consumption</i>	EPA Energy Star® compliant, Operating 140 W, Standby 27 W
<i>Main supply</i>	100/120/230 V, 50/60 Hz
<i>Dimensions</i>	52" (W) × 24" (D) × 45" (H)
<i>Weight</i>	150 lbs.

Océ Scan Logic® software

Océ Scan Logic is an optional scan-to-file software application for the Océ TDS320 multifunctional system.

<i>Applications</i>	Océ Scan Manager, integrated scanning solution and Océ View Station LT for viewing
<i>Scan destinations</i>	6 programmable destinations Scan to Web using FTP Scan to network directory Scan to controller
<i>Resolutions</i>	200, 300, 400 dpi
<i>Data formats</i>	Tiff (G3, G4, uncompressed) CALS Type 1 PDF
<i>Scan modes</i>	Single scan, stream feed productive batch scanning with or without check plot
<i>File naming</i>	Automatically generate unique file names for each scan, change file names at point of scanning
<i>Viewing</i>	View scans at point of scanning
<i>Océ Image Logic</i>	Optimum scan quality with special original modes
<i>Optimization</i>	Scan quality or file size
<i>Ease of use</i>	Scan to file from scanner panel, scan directly to destination
<i>Options</i>	■ Océ View Station for editing and enhancement of scanned documents ■ Océ Batch Processor for automated editing
<i>Minimum requirements</i>	Graphical user interface on Océ Power Logic Controller

Drivers and job-submission software

<i>Océ HDI driver</i>	For AutoCAD (LT) 2000, 2000i, 2002, 2004, 2005 and 2006
<i>Océ WPD</i>	Windows 2000, XP, Windows Server 2003, Windows Terminal Server, Citrix Metaframe
<i>Océ Adobe</i>	Windows 95, 98, ME, NT4.0, 2000, XP and Mac OS 9, X
<i>PostScript® 3 drivers</i>	
<i>OcéPrintExec® LT (optional)</i>	Individual Windows-based productive job creation and submission application with direct device feedback for Windows 2000, XP, and Windows Server 2003

